

**CAMERA PTZ CAMERA**



**PD-C-51-P**  
**5MP WDR IR PTZ Camera**

**FEATURES**

- 1/3" 5MP PS CMOS Image Sensor.
- 10/30fps@5MP (2592×1920).
- H.265 / H.264 triple-stream encoding.
- WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC.
- 18 times zoom lens.
- Auto-detect motivation and tracking.
- Day 1000m, IR Range of 120 Mtrs.
- IP67, IK10, ePoE.
- CMS Software: TerVMS.



**TECHNICAL SPECIFICATIONS**

Item/Model	PD-C-51-P
<b>Sensor:</b>	5 megapixel 1/3" CMOS; color 0.6 lux@F1.2; black and white 0.08 lux @F1.2; switch the filter; support conversion, day and night; sense of infrared; support the photosensitive resistance signal linkage; support the CS interface lens.
<b>RAM/FLASH:</b>	128MB/32MB.
<b>Lens:</b>	Focal length: 6 mm 108 mm; 18x optical zoom.
<b>Video Process:</b>	H.265/H.264 video coding; support triple-stream, AVI format; support adjustable stream 0.1M~6Mbps.
<b>Frame Rate:</b>	5 megapixel 10 frame, 3 megapixel 17 frame, 2 megapixel 25 frame, 1.3 megapixel and the following 30 frame, support 1~30 fps is adjustable.
<b>Video output:</b>	Main stream: 2592×1920, 2048×1536, 1920×1080, 1600×1200, 1280×1024, 1280×960, 1024×768, 1280×720. Sub stream: 704×576, 640×480, 640×360, 480×270, 352×288, 320×240, 352×192, 320×192, 288×192, 256×192.
<b>BLC Mode:</b>	WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC.
<b>Network interface:</b>	1*RJ45 Ethernet interface, 10/100M self-adaptation and can resist 6kv static electricity, support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/Upnp etc. network protocols.
<b>TF interface:</b>	1*TF/SD storage expansion interface(need to have a SD memory card socket).
<b>LED control interface:</b>	1* infrared light control interface, supports algorithm to control the opening and closing of infrared light.
<b>IR:</b>	IR range of 120 Mtrs, 8 IR LEDs.
<b>PTZ Pan/Tilt Range:</b>	Pan: 0° ~360°; Tilt: 0° ~90°; Rotation: 0° ~360°.
<b>Streaming Method:</b>	Unicast/Multicast.
<b>Max. User Access:</b>	10 Users/20 Users.
<b>Storage:</b>	NVR; Local PC for instant recording; SD memory card.
<b>Web Viewer:</b>	IE, Chrome, Firefox, Safari.
<b>CMS software:</b>	TerVMS (HiP2P Client).
<b>Optional features:</b>	W(WiFi), HW(power WiFi), E(POE power cable), C(EVDO wireless), G(WCDMA wireless), J(cell phone monitoring).
<b>Power:</b>	DC 12V input interface; 24W (38W with IR on) power consumption.
<b>Others:</b>	Restore the factory configuration button interface.

**ORDERING INFORMATION**

Model	Description
PD-C-51-P	5MP WDR IR PTZ Camera