

CAMERA 32CH H265 DVR



PD-DVR-32
32 Channel H265 DVR

FEATURES

- Smart H.265+/H.265/Smart H.264+/H.264.
- Max 128Mbps Incoming Bandwidth.
- Up to 4K (3840×2160) Resolution for Preview and Playback.
- HDMI/VGA simultaneous video output.

TECHNICAL SPECIFICATIONS

Item/Model	PD-DVR-32
System:	Embedded LINUX design, pure hardware decode, watchdog, hard disk storage, HDMI HD display, IP network video access. Main processor Hi3536C.
Video Input:	IP Camera access, each channel support dual stream access, support auto search, add, recording, preview and without debugging. Access bandwidth 128Mbps.
Video Output:	1 channel HDMI output, support 4K (3840×2160)/30Hz, 1920×1080, 1440×900, 1366×768, 1280×1024, 1280×800, 1024×768 resolution output show. 1 channel VGA output, homology with HDMI, support 1920×1080, 1440×900, 1366×768, 1280×1024, 1280×800, 1024×768 resolution output show. Support TerVMS client preview and seconds connection. 1/2/4/6/8/9/10/16/25/32 pictures real time preview.
Video recording:	Support 720P/960P/1080P/3MP/4MP/5MP/4K.
Video Capacity:	Support H.265+/H.265/H.264 decoding; DVR local recording playback support 4CH 2MP,2CH 4MP,1CH 4K; TerVMS client recording playback support 4 channels.
Audio:	Supports one 4 pin 3.5mm audio input and output jack (1 input 3.3V/1KΩ impedance, 2 output 2.8Vp-p/32Ωmin impedance, 1 GND). Standard G.711, support audio and video recording, support HDMI output channel preview and playback audio and video, TerVMS client audio and video preview and playback.
Storage:	2*SATA hard disk interface, support 8TB capacity; Support schedule record, motion detection linkage record; Support external USB storage devices (such as ordinary U disk, mobile hard disk) backup.
Network interface:	1*RJ45 Ethernet interface, support 10/100/1000M self-adaption; Support TCP/IP, IPv4, DHCP, NTP, RTSP, ONVIF, P2P, SMTP, GB28181 and so on protocols.
Max. User Access:	16 users.
Peripheral Interface:	2*USB2.0 interface(rear), support for the mouse, USB upgrade, import and export.
Front Panel:	1* power,1*record,1*network indicator light.
Functions:	Support preview/recording/forward/remote service, support alarm linkage, support TerVMS client remote control software.
Working Temperature:	-10°C ~ +55°C.
Working Humidity:	10% ~ 90%
Power:	DC +12V/4A power input, host power consumption ≤ 3W (No disk).

ORDERING INFORMATION

Model	Description
PD-DVR-32	32 channel H265 DVR